

匯統國際股份有限公司
Huey Tung International Co.,

產品規格書 Specification

[Model : HTPA-5288 / 2024.06.17 version]



Cara Audio Corporation

No.69, Lane 762, Dingzhong Road, Sanmin District, Kaohsiung City, Taiwan, ROC.


Tel: 886-7-310 5786 / Fax: 886-7-310 0783

E-mail: carawang@hueytung.com.tw / <http://www.hueytung.com.tw>

揚聲器製品規格書

SPEAKER SPECIFICATION

型號 Model Number: HTPA-5288 (G260)

項目 Items		規格 Specification			
1	直流阻抗 DCR	6.8±15%Ω			
2	額定阻抗 Rated Impedance	8±15%Ω			
3	最低共振周波数 Lowest Resonance Frequency	50Hz±20%Hz Without a baffle			
4	实效周波数带域 Effective Frequency Range	F0~20KHz -10dB			
5	出力音压 Output Sound Pressure Level	88dB±3dB 1W/1M at (600,800,1000,1200)Hz AVE.			
6	入力 Input	定格入力 Rated input 15 W	最大入力 Maximum input 30 W		
7	磁束密度 Flux Density	GAUSS			
8	异常音试验电压 Buzz & Rattle Test	Must be normal at sine wave 10.95 V , 40Hz -3KHz			
9	动作试验电压 Operation Test	Must be normal at sine wave			
10	极性 Polarity	从 SPK 端子正极输入直流正电压另一端输入负电压时，振动板向前推动。 When a positive volts d.c.is supplied from the speaker terminal marked(+)and a Negative volts to the other terminal the diaphragm must move toward the front			
11	磁石尺寸/重量 Magnet Dimension/Weigh	Magnet: Φ90*Φ45*15mm , Ferrite Sub Magnet: /	Magnet:/ Sub Magnet: /		
12	连续负荷试验 Life Test	Pink noise 15 W 8 hours	After the Test, Speaker should be meet the Outside and item 7,8		
13	耐热试验 Heat Resistance	55°C±2°C 16Hours			
14	耐湿试验 Humidity Resistance	90%-95%RH 48Hours			
15	耐寒试验 Cold Resistance	-20°C±2°C 8Hours			
16	绝缘耐压试验 Insulation Resistance	Or more 1MΩ 以上			
17	周波数特性 Frequency Response Curve	参照附图 On Other Drawing			
18	失真率 Distortion	/			
19	音圈规格材質 Voice coil material & size	ASV Φ30.5/2L			
20	尺寸 Dimension	詳見外形圖 See detail from figure chart			
21	总重量 Total Weight	1600g±20% or oz			
		Size: 5" 試作發行: 2024. 6.17	Approve: Arthur	Check: John	Design: Wang

