

匯統國際股份有限公司  
Huey Tung International Co.,

# 產品規格書 Specification

[ Model : HTPA-6415 / 2024.06.17 version ]



**Cara Audio Corporation**

No.69, Lane 762, Dingzhong Road, Sanmin District, Kaohsiung City, Taiwan, ROC.


Tel: 886-7-310 5786 / Fax: 886-7-310 0783

E-mail: [carawang@hueytung.com.tw](mailto:carawang@hueytung.com.tw) / <http://www.hueytung.com.tw>

# 揚聲器製品規格書

## SPEAKER SPECIFICATION

型號 Model Number: HTPA-6415 (G260)

項目 Items		規格 Specification		
1	直流阻抗 DCR	6.8±15%Ω		
2	額定阻抗 Rated Impedance	8±15%Ω		
3	最低共振周波数 Lowest Resonance Frequency	45Hz±20%Hz Without a baffle		
4	实效周波数带域 Effective Frequency Range	F0~20KHz -10dB		
5	出力音压 Output Sound Pressure Level	88dB±3dB 1W/1M at (600,800,1000,1200)Hz AVE.		
6	入力 Input	定格入力 Rated input	最大入力 Maximum input	
		15 W	30 W	
7	磁束密度 Flux Density	GAUSS		
8	异常音试验电压 Buzz & Rattle Test	Must be normal at sine wave 10.95 V , 35Hz -3KHz		
9	动作试验电压 Operation Test	Must be normal at sine wave		
10	极性 Polarity	从 SPK 端子正极输入直流正电压另一端输入负电压时，振动板向前推动。		
		When a positive volts d.c.is supplied from the speaker terminal marked(+)and a Negative volts to the other terminal the diaphragm must move toward the front		
11	磁石尺寸/重量 Magnet Dimension/Weigh	Magnet: Φ85*Φ32*18mm , Ferrite	Magnet:/	
		Sub Magnet: /	Sub Magnet:/	
12	连续负荷试验 Life Test	Pink noise 15 W 8 hours	After the Test, Speaker should be meet the Outside and item 7,8	
13	耐热试验 Heat Resistance	55°C±2°C 16Hours		
14	耐湿试验 Humidity Resistance	90%-95%RH 48Hours		
15	耐寒试验 Cold Resistance	-20°C±2°C 8Hours		
16	绝缘耐压试验 Insulation Resistance	Or more		
		1MΩ 以上		
17	周波数特性 Frequency Response Curve	参照附图		
		On Other Drawing		
18	失真率 Distortion	/		
19	音圈规格材质 Voice coil material & size	ASV Φ25.5/2L		
20	尺寸 Dimension	详见外形图 See detail from figure chart		
21	总重量 Total Weight	1730g±20% or oz		
	Size: 6"	Approve:	Check:	Design:
	試作發行: 2024. 6.17	Arthur	John	Wang

