




# 揚聲器製品規格書

## SPEAKER SPECIFICATION

型號 Model Number: HT-6279 (G090611)

項目 Items		規格 Specification	
1	公称阻抗 Nominal Impedance	4Ω±15% at 250 Hz	
2	最低共振频率 Lowest Resonance Frequency	45 Hz±20%Hz Without a baffle	
3	实效周波数带幅 Effective Frequency Range	F0~20KHz -10dB	
4	出力音压 Output Sound Pressure Level	86dB±2dB 1W/1M at (100,200,300,400)Hz AVE.	
5	入力 Input	定格入力 Rated input 40 W	最大入力 Maximum input 80 W
6	磁束密度 Flux Density	-----±10% GAUSS	
7	异常音试验电压 Buzz & Rattle Test	Must be normal at sine wave 8.9 V	
8	动作试验电压 Operation Test	Must be normal at program source 8.9 V	
9	极性 Polarity		
10	磁石尺寸/重量 Magnet Dimension/Weight	Magnet: 9. 97 Sub Magnet:	/G
11	连续负荷试验 Life Test	Peak Noise 40 W 48 hours	After the Test, Speaker should be meet the Outside and item 7,8
12	耐热试验 Heat Resistance	70°C±2°C 20%-25%RH 8Hours and then room temperature 1 hours	
13	耐湿试验 Humidity Resistance	40°C±2°C 50%-95%RH 8Hours and then room temperature 1 hours	
14	耐寒试验 Cold Resistance	-25°C±2°C 8Hours and then room temperature 1 hours	
15	落下试验 Drop Test	1M 75°±2°	
16	绝缘耐压试验 Insulation Resistance	Or more 1MΩ 以上	
17	周波数特性 Frequency Response Curve	参照附图 On Other Drawing	
18	失真率 Distortion	5% MAX	
19	各部 材质	Cone Paper	Paper+ Rubber Edge
		Voice Coil	/
		Cap	/
20	总重量 Total Weight	/	
	Size: 6.5"	Approve:	Check:
	試作發行: 2009.10.13	Arthur	Tang
		Design:	LIU

