



匯統國際股份有限公司
Huey Tung International Co., Ltd.

產品規格書 Specification

[Model : HT-6378 / 2015.9.9 version]



Cara Audio Corporation


No.69, Lane 762, Dingzhong Road, Sanmin District, Kaohsiung City, Taiwan, ROC.

Tel: 886-7-310 5786 / Fax: 886-7-310 0783

E-mail: carawang@hueytung.com.tw / <http://www.hueytung.com.tw>

揚聲器製品規格書

SPEAKER SPECIFICATION

型號 Model Number: HT-6378					
項目 Items		規格 Specification			
1	公称阻抗 Nominal Impedance	4Ω±15% at 20°C 500Hz 100mA			
2	最低共振周波数 Lowest Resonance Frequency	82 Hz±20%Hz Without a baffle			
3	实效周波数带域 Effective Frequency Range	F0-20KHz			
4	出力音压 Output Sound Pressure Level	88dB±3dB 1W/1M at (1000 , 1200 , 1500 , 2000) Hz AVE.			
5	入力 Input	定格入力 Rated input 45W	最大入力 Maximum input 90W		
6	磁束密度 Flux Density	-----±10% GAUSS			
7	异常音试验电压 Buzz & Rattle Test	Must be normal at sine wave			
8	动作试验电压 Operation Test	Must be normal			
9	极性 Polarity	When a positive DC current is applied title voice coil terminal marked the diaphragm shall move forward			
10	磁石尺寸/重量 Magnet Dimension/Weigh	Magnet: 80x40x15 Y30 Sub Magnet:	10oz		
11	连续负荷试验 Life Test	45W 24 hours	After the Test, Speaker should be meet the Outside and item 7,8		
12	耐热试验 Heat Resistance	70°C±2°C 20%-50%RH 96Hours and then room temperature 1 hour			
13	耐湿试验 Humidity Resistance	40°C±2°C 90%-95%RH 96Hours and then room temperature 1 hour			
14	耐寒试验 Cold Resistance	-30°C±2°C 96Hours			
15	落下试验 Drop Test	60cm at 60°			
16	绝缘耐压试验 Insulation Resistance	Or more 1MΩ 以上			
17	周波数特性 Frequency Response Curve	参照附图 On Other Drawing			
18	失真率 Distortion	1.2fo<f≤500Hz 時 ≤7% ; 500<f≤5000Hz 時 ≤3%			
19	各部 材质	Cone Paper	W: PP. injection + Rubber Edge T: 41mm PEI		
		Voice Coil	KSV 25 mm		
		Cap	/		
20	总重量 Total Weight				
		Size: Φ 166mm 68mmH 試作發行: 2015.09.09	Approve: Arthur	Check: John	Design: WANG

