

匯統國際股份有限公司
Huey Tung International Co., Ltd.

產品規格書 Specification

[Model : HTW-1805 / 2003.06.02 version]



Cara Audio Corporation

No.69, Lane 762, Dingzhong Road, Sanmin District, Kaohsiung City, Taiwan, ROC.


Tel: 886-7-310 5786 / Fax: 886-7-310 0783

E-mail: carawang@hueytung.com.tw / <http://www.hueytung.com.tw>

揚聲器製品規格書

SPEAKER SPECIFICATION

型號 Model Number: HTW-1805

項目 Items		規格 Specification		
1	公称阻抗 Nominal Impedance	8Ω±15% at 200 Hz		
2	最低共振周波数 Lowest Resonance Frequency	40 Hz±8Hz Without a baffle		
3	实效周波数带域 Effective Frequency Range	F0~4KHz -10dB		
4	出力音压 Output Sound Pressure Level	100dB±2dB 1W/1M 2.83V		
5	入力 Input	定格入力 Rated input 100 W	最大入力 Maximum input 600 W	
6	磁束密度 Flux Density	-----±10% GAUSS		
7	异常音试验电压 Buzz & Rattle Test	Must be normal at sine wave 15 V		
8	动作试验电压 Operation Test	Must be normal at program source		
9	极性 Polarity	/		
10	磁石尺寸/重量 Magnet Dimension/Weigh	Magnet:220*20 mm Sub Magnet:	2851G	
11	连续负荷试验 Life Test	EIA Pink Noise 100 W 24 hours	After the Test, Speaker should be meet the Outside and item 7,8	
12	耐热试验 Heat Resistance	70°C±2°C 20%-25%RH 48Hours and then room temperature 1 hour		
13	耐湿试验 Humidity Resistance	43°C±2°C 90%-95%RH 24Hours and then room temperature 1 hour		
14	耐寒试验 Cold Resistance	- 25°C±3°C 48Hours and then room temperature 1 hour		
15	落下试验 Drop Test	1M 75°±2°		
16	绝缘耐压试验 Insulation Resistance	Or more 1MΩ 以上		
17	周波数特性 Frequency Response Curve	参照附图 On Other Drawing		
18	失真率 Distortion	/		
19	各部 材质	Cone Paper	/	
		Voice Coil	KSV, diameter 99.3mm, length 20.2mm	
		Cap	/	
20	总重量 Total Weight	11300G		
	Size: 464mm 試作發行:	Approve: Arthur	Check: John	Design: WANG



音統國際股份有限公司

版權所有